



GEARHEAD, HELICAL, 10:1  
(METERING PUMPS)



**SPECIFICATIONS:**

SERVO MOTOR DUTY  
 INERTIA: 0.44 – 0.61 KG/CM  
 MASS: 3.7 KG  
 PROTECTION: IP65  
 STANDARD BACKLASH: 5 ARCMIN  
 CONTINUOUS SPEED: ~4000 RPM  
 MAXIMUM (INTERMITTENT) SPEED: ~8000 RPM  
 KEYED SHAFT OPTION

INSTALLATION / SPECIAL NOTES:

REV	DESCRIPTION	DATE	APPROVED
-	-	-	-
-	-	-	-
-	-	-	-



REVISIONS	STANDARD TOLERANCES UNLESS OTHERWISE SPECIFIED		DIMENSIONS INCH [MM]		 Sussex, Wisconsin (262) 372-4515
	DECIMAL DIMENSIONS:		CHECKED BY	PROJECT ENG.	
	ONE PLACE	±.10" ±2.5mm	DRAWN BY	DATE	TITLE
	TWO PLACE	±.02" ±0.5 mm			TPP
	THREE PLACE	±.004" ±0.10 mm	REFERENCE NO.	SCALE:	DWG NO.
ANGLE	±1/2° ±1/2°	ORG. WORK ORDER NO.	N/A	840-778-1003	
CONFIDENTIAL THIS DRAWING AND THE INFORMATION CONTAINED HEREON ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF GENCOAT INC. REPRODUCTION/COPYING OR DISCLOSURE OF THIS DRAWING TO OTHERS WITHOUT GENCOAT'S WRITTEN PERMISSION IS PROHIBITED. THIS DRAWING AND ANY CORRECTIONS THEREOF, SHALL IMMEDIATELY BE RETURNED TO GENCOAT UPON REQUEST BY GENCOAT. BY PURSUING THIS DRAWING, GENCOAT GRANTS NO RIGHTS OR LICENSES NOR MAKES ANY REPRESENTATIONS OR WARRANTIES REGARDING THIS DRAWING OR THE ACCOMPANYING INFORMATION. THE CONTENTS OF THESE DRAWINGS MAY BE PROTECTED BY UNITED STATES AND/OR FOREIGN COPYRIGHTS OR PATENTS.		 3RD ANGLE PROJECTION		SHEET: 1 OF 1	