

OUT

IN



SPIN-ON FILTER HERE

SPECIFICATIONS:

PORT THREAD: 3/4" NPT

FILTER THREAD: 1 3/8-12 UN

BYPASS: 25 PSI (1.7 BAR)

INSTALLATION / SPECIAL NOTES:



TYPICAL USE:

- INLET HEAD FOR TANK OIL SPIN-ON SUPPLY FILTERS

* CONSULT W/GFG FOR REPLACEMENT SPIN-ON FILTER ELEMENTS FOR OIL APPLICATIONS



REV	DESCRIPTION	DATE	APPROVED
-	-	-	-
-	-	-	-

REVISIONS	STANDARD TOLERANCES UNLESS OTHERWISE SPECIFIED		DIMENSIONS INCH [MM]		 Sussex, Wisconsin (262) 691-0400
	DECIMAL DIMENSIONS:		CHECKED BY	PROJECT ENG.	
	ONE PLACE	±.10" ±2.5mm	DRAWN BY TPP	DATE 1/15/20	TITLE HEAD, SPIN-ON FILTER, HYDRAULIC PART DRAWING
	TWO PLACE	±.02" ±0.5 mm		REFERENCE NO.	SCALE: DWG NO.
THREE PLACE	±.004" ±0.10 mm	ORIG. WORK ORDER NO.	N/A	H130-2830	
ANGLE	±1/2' ±1/2'	 3RD ANGLE PROJECTION		SHEET: 1 OF 1	