



SPECIFICATIONS:
 22 MICRON FILTRATION
 MEDIA: SYNTHETIC
 CANISTER SEAL (O-RING): NITRILE

PRESSURE MAX: 10 BAR (AT 50° C)
 TEMP. MAX: 121° C


INSTALLATION / SPECIAL NOTES:

TYPICAL USE:
 - TANK OIL SUPPLY FILTER

* CONSULT W/GFG FOR OTHER REPLACEMENT
 FILTER ELEMENTS FOR OTHER OIL APPLICATIONS



REV	DESCRIPTION	DATE	APPROVED
-	-	-	-
-	-	-	-

REVISIONS	STANDARD TOLERANCES UNLESS OTHERWISE SPECIFIED	DIMENSIONS INCH [MM]		 Sussex, Wisconsin (262) 691-0400
	DECIMAL DIMENSIONS:	CHECKED BY	PROJECT ENG.	
	ONE PLACE ±.10" ±2.5mm	DRAWN BY TPP	DATE 12/06/19	
	TWO PLACE ±.02" ±0.5 mm		REFERENCE NO.	
THREE PLACE ±.004" ±0.10 mm	ORG. WORK ORDER NO.		TITLE FILTER, SPIN-ON, HYDRAULIC, 22u PART DRAWING	
ANGLE ±1/2" ±1/2"	 3RD ANGLE PROJECTION		SCALE: N/A	DWG NO. H130-2831
<small>THIS DRAWING AND THE INFORMATION CONTAINED HEREIN ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF GENCOAT INC. REPRODUCTION/COPYING OR DISCLOSURE OF THIS DRAWING TO OTHERS WITHOUT GENCOAT'S WRITTEN PERMISSION IS PROHIBITED. THIS DRAWING, AND ANY COPIES THEREOF, SHALL IMMEDIATELY BE RETURNED TO GENCOAT UPON REQUEST BY GENCOAT. IN FURNISHING THIS DRAWING, GENCOAT GRANTS NO RIGHTS OR LICENSES NOR MAKES ANY REPRESENTATIONS OR WARRANTIES REGARDING THIS DRAWING OR THE ACCOMPANYING INFORMATION. THE CONTENTS OF THESE DRAWINGS MAY BE PROTECTED BY UNITED STATES AND/OR FOREIGN COPYRIGHTS OR PATENTS.</small>				SHEET: 1 OF 1