



CONNECTION: 1/4" NPT (FEMALE) THREAD  
 PRESSURE: 250 PSI, 17.3 BAR MAXIMUM  
 TEMPERATURE: 400°F MAX. CONTINUOUS  
 MATERIALS:  
 BODY: CHROME-PLATED BRASS  
 THUMB LATCH: STAINLESS STEEL  
 VALVE: NONE  
 VALVE SPRINGS: NONE  
 EXTERNAL SPRINGS AND PIN: STAINLESS STEEL  
 O-RINGS: VITON  
 COLOR: CHROME

REV	DESCRIPTION	DATE	APPROVED

REVISIONS	STANDARD TOLERANCES UNLESS OTHERWISE SPECIFIED		DIMENSIONS INCH [MM]		Sussex, Wisconsin (262) 691-0400
	DECIMAL DIMENSIONS: ONE PLACE ±.10" TWO PLACE ±.02" THREE PLACE ±.004" ANGLE ±1/2° ±0.10 mm		CHECKED BY	PROJECT ENG.	
	CONFIDENTIAL THIS DRAWING AND THE INFORMATION CONTAINED HEREIN ARE CONFIDENTIAL AND THE EXCLUSIVE PROPERTY OF GFG. REPRODUCTION/COPYING OR DISCLOSURE OF THIS DRAWING TO OTHERS WITHOUT GFG'S WRITTEN PERMISSION IS PROHIBITED. THIS DRAWING, AND ANY COPIES THEREOF, SHALL IMMEDIATELY BE RETURNED TO GFG UPON REQUEST BY GFG. IN FURNISHING THIS DRAWING, GFG GRANTS NO RIGHTS OR LICENSES NOR MAKES ANY REPRESENTATIONS OR WARRANTIES REGARDING THIS DRAWING OR THE ACCOMPANYING INFORMATION. THE CONTENTS OF THESE DRAWINGS MAY BE PROTECTED BY UNITED STATES AND/OR FOREIGN COPYRIGHTS OR PATENTS.		DRAWN BY	DATE	SCALE: DWG NO. NTS 7195-0611
			SJA	05/03/07	
			3RD ANGLE PROJ.		DO NOT SCALE DRAWING
				SHEET: 1 OF 1	